

Hudson Marine International

DIESEL OUTBOARD MOTORS

Hudson Marine International is delighted to offer these exclusive diesel outboard engines for global delivery.

These low revving, high thrust, outboard engines are ideally suited to locations where the cost of fuel is high and where economy and reliability are priorities.

The 6 HP diesel outboard engine pictured will consume approximately 1.4 litres per hour and is quite capable of propelling an 8m vessel weighing 2 tonnes.

A full range of diesel outboard engines from 4 HP up to 20 HP is available.

Contact Hudson Marine International via our website www.hudsonmarineinternational.com for details of your local HMI distributor.

Specifications for the 4, 9, 12 and 20 HP are on the following pages.



HMI 6 HP DIESEL OUTBOARD MOTOR

ENGINE TYPE	SINGLE CYLINDER, FOUR STROKE, AIR COOLED, DIRECT INJECTION
Bore x Stroke	70mm x 62mm
Displacement	0.296 litres
Power	6 HP
Starting	Electric Start with Manual Backup
Built-in Fuel Tank Capacity	3.5 litres
Fuel Consumption	1.4 litres / hour
Net Weight	≤69 kg
Diameter of Standard Propeller	380 mm
Shaft Length	Long and Extra Long. Custom shaft length also available.
Application	5m – 8m vessel of 2 tonnes maximum laden weight.

Hudson Marine International

Hudson Marine International

DIESEL OUTBOARD MOTORS

HMI 4 HP DIESEL OUTBOARD MOTOR

ENGINE TYPE	SINGLE CYLINDER, FOUR STROKE, AIR COOLED, DIRECT INJECTION
Bore x Stroke	70mm x 55mm
Displacement	0.211 litres
Power	4 HP
Starting	Electric Start with Manual Backup
Built-in Fuel Tank Capacity	2.5 litres
Fuel Consumption	1.2 litres / hour
Net Weight	≤61 kg
Diameter of Standard Propeller	340 mm
Shaft Length	Long and Extra Long. Custom shaft length also available.
Application	4m – 7m vessel of 1 tonne maximum laden weight.

HMI 9 HP DIESEL OUTBOARD MOTOR

ENGINE TYPE	SINGLE CYLINDER, FOUR STROKE, AIR COOLED, DIRECT INJECTION
Bore x Stroke	86mm x 72mm
Displacement	0.418 litres
Power	9 HP
Starting	Electric Start with Manual Backup
Built-in Fuel Tank Capacity	5.5 litres
Fuel Consumption	1.6 litres / hour
Net Weight	≤84 kg
Diameter of Standard Propeller	380 mm
Shaft Length	Long and Extra Long. Custom shaft length also available.
Application	7m – 10m vessel of 3 tonnes maximum laden weight.



HMI 9 HP Diesel OBM

Hudson Marine International

Hudson Marine International

DIESEL OUTBOARD MOTORS

HMI 12 HP DIESEL OUTBOARD MOTOR

ENGINE TYPE	SINGLE CYLINDER, FOUR STROKE, AIR COOLED, DIRECT INJECTION
Bore x Stroke	88mm x 75mm
Displacement	0.456 litres
Power	12 HP
Starting	Electric Start with Manual Backup
Built-in Fuel Tank Capacity	5.5 litres
Fuel Consumption	2 litres / hour
Net Weight	≤84 kg
Diameter of Standard Propeller	380 mm
Shaft Length	Long and Extra Long. Custom shaft length also available.
Application	7m - 13m vessel of 4 tonnes maximum laden weight.

HMI 20 HP DIESEL OUTBOARD MOTOR

ENGINE TYPE	V TWIN CYLINDER, FOUR STROKE, AIR COOLED, DIRECT INJECTION
Bore x Stroke	88mm x 75mm
Displacement	0.912 litres
Power	20 HP
Starting	Electric Start with Manual Backup
Built-in Fuel Tank Capacity	12 litres
Fuel Consumption	4.5 litres / hour
Net Weight	≤110 kg
Diameter of Standard Propeller	370 mm
Shaft Length	Long and Extra Long. Custom shaft length also available.
Application	8m - 15m vessel of 7 tonnes maximum laden weight.



HMI 20 HP Diesel OBM

Hudson Marine International